COR-IP2TRFE



2MP IP Mini Turret Camera with 3.6mm Fixed Lens & Built-In Microphone





KEY FEATURES

- 2MP 1920 (H) x 1080 (V)
- 3.6mm Wide Angle Lens
- Built-in Microphone
- All Metal Housing IP67
- Small Size





/MS Pro

SPECIFICATIONS		On-Board Storage
*VIDEO		Alarm
Imaging Device	1/2.7" Progressive CMOS	Audio
Effective Pixels	2MP 1920(H)×1080(V)	Hardware Reset
Scanning System	Progressive CMOS	*NETWORK
Min. Illumination	Color 0.006lux @ F1.6(AGC ON); B/W 0 lux @ IR ON	Ethernet
*LENS TYPE		Video Compressio
Focal Length (Zoom Ratio)	3.6mm wide angle lens	Video Quality Adju
Max. Aperture Ratio	F No. 2.2	Resolution
Angular Field of View	Horizontal: 86°, Vertical: 47°, Diagonal: 105°	
Min. Object Distance	2m	
Lens Type	Fixed(M12)	Bitrate control met
*OPERATIONAL		Streaming Capabi
IR Viewable Length	Up to 30m	Protocol
Camera Title	On/Off	Security
Day & Night	IR cut filter with auto switch(Day/Night/Auto/Image/ Schedule)	
Backlight Compensation	Off/On (5 Zone)	Application Progra
Wide Dynamic Range	DWDR	Web Viewer
Digital Noise Reduction	3D DNR	*PHYSICAL
Motion Detection	Off/On (8 Level)	Material / Protectio
Privacy Masking	Off/On (4 Zone, Rectangle)	Operating Condition
Gain Control	Auto	Input Voltage / Cu
White Balance	Auto/Manual	Max Power Consu
Electronic Shutter Speed	1/5 ~ 1/20000s	Dimension (L x W
Mirror	Flip/Rotation	Weight

On-Board Storage	Micro SD slot, up to 256GB		
Alarm	NA		
Audio	Built-in microphone		
Hardware Reset	Yes		
*NETWORK			
Ethernet	RJ45 (10/100 Base-T)		
Video Compression Format	H.265+ / H.265 / H.264		
Video Quality Adjustment	256Kbps ~ 4Mbps		
Resolution	Main Stream @30fps 1080P (1920 x 1080) Sub Steam @20fps VGA (640 x4 80)"		
Bitrate control method	Constant (CBR) / Variable (VBR)		
Streaming Capability / Method	Dual Stream (Main/Sub) / Unicast / Multicast		
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP		
Security	IP address filter;complicated password; Authenticated user name and password		
Application Programming Interface	Open Compatibility, (Profile S / G / T / M)		
Web Viewer	IIE10/11, Safari V12.1 above, Firefox V.52 above, Google chrome V.57 above, Edge V.79 above		
*PHYSICAL			
Material / Protection	Metal Housing / IP67		
Operating Conditions	Temp: -35~+60°C / Humidity: less than ≤ 95% RH		
Input Voltage / Current	DC12V or POE 48V (IEEE802.3af)		
Max Power Consumption	3.5-5W		
Dimension (L x W x H)	100 x 100 x 90 mm (3.93 x 3.93 x 3.54 inches)		
Weight	Approximately 282g (.91 lbs)		





©2024 Cortex® As our product is subject to continuous improvement, Cortex & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incurring any obligation. E&OE. Distributed by www.cortexcetv.com 01-11132024