


2MP TURRET NETWORK CAMERA with Wide Angle Lens



KEY FEATURES

- 1/3" ColorMax Progressive CMOS
- Wide Angle IR Lens
- Digital Noise Reduction
- Built-in-Microphone
- Supports infrared dual supplementary light
- Maximum Resolution 1920x1080@25fps
- Strong Light Suppression
- Dual Streaming
- IR Range up to 98 feet
- Metal Housing / IP66 Waterproof



SPECIFICATIONS

Video Compression Format	H.265+ / H.265 / H.264
Imaging Device	1 / 3" ColorMax Progressive CMOS
Effective Pixels	2MP 1920(H)×1080(V)
Scanning System	Progressive CMOS
Min. Illumination	Color 0.008lux @ F1.6(AGC ON) ; B/W 0 lux @ IR ON
Video Quality Adjustment	256Kbps ~ 2Mbps
Electronic Shutter Speed	1/5 ~ 1/20000s
Focal Length (Zoom Ratio)	2.8mm wide angle lens
Max. Aperture Ratio	F 1.6
Angular Field of View	Horizontal: 97°, Vertical:52°, Diagonal:115°
Min. Object Distance	2m
Lens Type	Fixed Wide Angle (M12)
Camera Title	On / Off
Day & Night	IR cut filter with auto switch(Day/Night/Auto/Image/Schedule)
IR LED	2
IR Viewable Length	Up to 98.4 feet (30m)
Backlight Compensation	Off/On (4 Zone)
Wide Dynamic Range	WDR
Digital Noise Reduction	3D DNR
Motion Detection	Off / On (8 Level)
Image Settings	Day&Night Mode / Schedule
Privacy Masking	Off / On (4 Zone, Rectangle)

Audio	Built-in microphone
White Balance	Auto / Manual
Alarm	N/A
Smart Feature	Human&Vehicle Detection (PD&VD) Perimeter Intrusion Detection(PID) Line Crossing Detection(LCD)
*NETWORK	
IP / Ethernet	IPv6 / RJ45(10/100BASE-T)
Resolution	Main Stream &30fps 1080P(1920x1080) Sub Stream &20fps VGA(640x480)
Bitrate control method	CBR/VBR
Streaming Capability	Dual-Stream(Main/Sub)
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,SMTP,NTP,UPnP,SNMP,HTTPS,FTP
Security	IP address filter;complicated password;Authenticated username and password
Streaming Method	Unicast / Multicast
Web Viewer	IE10/11
*PHYSICAL	
Material / Protection	Metal Housing / IP66 Waterproof
Operating Conditions	Temp: -35~+60°C/ Humidity: less than ≤ 95% RH
Input Voltage / Current	DC12V / POE (IEEE802.3af)
Power Consumption	DC12V:max 2.18W; POE(48V): max 2.78W
Dimension (W x H x D)	89 x 89 x 76.5mm (3.5 x 3.5 x 3.1 inches)
Weight	Approximately 238g (.52 lbs)

COR-IP2TRM

