



MEDALLION SERIES™



KEY FEATURES

- 4K (8MP) 3840 (H) × 2160 (V)
- 2.8mm IR Wide Angle Lens
- Dual Lighting - IR & ColorMAX®
- Built in Microphone
- Essential AI
- All Metal Housing IP67



SPECIFICATIONS	
*VIDEO	
Imaging Device	1 / 2.7" Progressive ColorMax CMOS
Effective Pixels	8MP (4K) 3840 (H) × 2160 (V)
Scanning System	ColorMAX Progressive CMOS
Min. Illumination	Color 0.009lux @ F1.6 (AGC ON); B/W 0 lux @ IR ON
*LENS TYPE	
Focal Length (Zoom Ratio)	2.8mm wide angle lens
Max. Aperture Ratio	F No. 1.6
Angular Field of View	Horizontal: 110°, Vertical: 58°, Diagonal: 132°
Min. Object Distance	2m
Lens Type	Fixed (M12)
*OPERATIONAL	
IR LED	1
ColorMAX Light	2
IR Viewable Length	Up to 65ft
ColorMAX Light Viewable Length	Up to 60ft
Type of complementary light	IR / ColorMAX selectable
Motion Detection	Off/On (8 Levels)
Wide Dynamic Range	DWDR
Digital Noise Reduction	3D DNR
Image Setting	Full Color Mode / Day & Night Mode / Smart Illumination
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 256GB
Alarm	NA
Audio	Built-in microphone
Hardware Reset	Yes

Smart Feature	Face Detection (FD) Human&Vehicle Detection (PD&VD) Perimeter Intrusion Detection (PID) Line Crossing Detection (LCD) Cross Counting (CC) Stationary Object Detection (SOD) Heat Map (HM) Crowd Density Detection (CD) Queue Length Detection (QD) License Plate Detection (LPD) Rare Sound Detection (RSD)
*NETWORK	
Ethernet	RJ45 (10/100 Base-T)
Video Compression Format	H.265+ / H.265 / H.264
Video Quality Adjustment	256Kbps ~ 16Mbps
Resolution	Main Stream @20fps 8MP(3840x2160), 5MP(2592x1944,3072x1728), 4MP(2592x1520), 3MP(2304x1296), 1080P(1920x1080), 960P(1280x960), 720P(1280x720) Sub Stream @20fps 720P(1280x720), VGA(640x480), QVGA(320x240) Mobile Stream @20fps VGA(640x480), QVGA(320x240)
Bitrate control method	Constant (CBR) / Variable (VBR)
Streaming Capability / Method	Triple-Stream (Main/Sub/Mobile) / Unicast / Multicast
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Security	IP address filter; complicated password; Authenticated username and password
Application Programming Interface	Open Compatibility, (Profile S / G / T / M)
Web Viewer	IIE10/11, Safari V12.1 above, Firefox V.52 above, Google chrome V.57 above, Edge V.79 above
*PHYSICAL	
Material / Protection	Metal Housing / IP67
Operating Conditions	Temp: -35~+60°C / Humidity: less than ≤ 95% RH
Input Voltage / Current	DC12V or POE 48V (IEEE802.3af)
Max Power Consumption	3-5.5W
Dimension (W x H x D)	100 x 100 x 90 mm (3.9 x 3.9 x 3.5 inches)
Weight	Approximately 415g (.91 lbs)

COR-IP8TRFEG

